

# Air Compressors

## Sullair® Compressors & Parts



### APPLICATION

Prior Power Solutions is an official dealer of Sullair® compressors and parts.

The Sullair® ShopTek ST4-ST15 CE rotary screw air compressors redefine industry standards for continuous duty compressors in the 4-15 kW range.

Designed with the end customer in mind, ShopTek compressors feature a small footprint and are built to provide exceptional reliability with extremely low maintenance.



### Features

- Legendary Sullair® air end
- 10,000 hour genuine Sullube® factory fill
- 5-year Emerald Warranty - providing coverage on major components including the air end, air/fluid receiver main drive motor, fluid cooler and aftercooler.

### Genuine Sullube® by Sullair®

- Protects and cleans (no varnish)
- Controls operating temperatures
- Optimal viscosity
- Environmentally-friendly
- Reduces fluid point (263°C)

### Technical Specifications

Model	8 Bar m <sup>3</sup> /min	10 Bar m <sup>3</sup> /min	kW	Starter	dBa Rating	Machine Weight (kg)	Length (mm)	Width (mm)	Height (mm)
<b>ST4</b>	0.58	0.5	4	Full Voltage	64	238	826	546	940
<b>ST5</b>	0.83	0.75	5	Full Voltage	66	238	826	546	940
<b>ST7</b>	1.07	1.01	7	Full Voltage	66	238	826	546	940
<b>ST11</b>	1.8	1.55	11	Y-Delta	66	350	998	618	1035
<b>ST15</b>	2.28	2.05	15	Y-Delta	68	365	998	618	1035
<b>ST18</b>	2.9	2.6	18.5	Y-Delta	68	610	1340	740	1315
<b>ST18V</b>	3	2.6	18.5	VSD	68	680	1690	740	1315
<b>ST22</b>	3.55	3.1	22	Y-Delta	68	660	1340	740	1315
<b>ST22V</b>	3.6	3.1	22	VSD	68	780	1690	740	1315
<b>ST30</b>	4.75	4.1	30	Y-Delta	75	950	1700	935	1450
<b>ST30V</b>	4.75	4.25	30	VSD	75	1050	2050	935	1450
<b>ST37</b>	6.3	5.8	37	Y-Delta	75	1050	1700	935	1450
<b>ST37V</b>	6.3	5.8	37	VSD	75	1150	2050	935	1450

\* 380-415V Motor

\*50Hz

\*Dimensions provided are unpackaged

